

MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

AD



FORECAST AIDS FOR PREDICTING TROPICAL CYCLONE ASSOCIATED GUSTS AND SUSTAINED WINDS FOR YOKOSUKA, JAPAN

Prepared By:

J. D. Jarrell and R. E. Englebretson Science Applications, Inc. Monterey, California 93940

Contract No. NO0228-81-C-H361

AUGUST 1982

APPROVED FOR PUBLIC RELEASE DISTRIBUTION UNLIMITED



Prepared For:

NAVAL ENVIRONMENTAL PREDICTION RESEARCH FACILITY MONTEREY, CALIFORNIA 93940

SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM								
	3. RECIPIENT'S CATALOG NUMBER								
Contractor Report CR 82-11 AD-A/8/1	80								
4. TITLE (and Subtitle)	S. TYPE OF REPORT & PERIOD COVERED								
Forecast Aids for Predicting Tropical Cyclone	Final								
Associated Gusts and Sustained Winds for	6. PERFORMING ORG. REPORT NUMBER								
Yokosuka, Japan	SAI PN-1-425-08-453								
7. AUTHOR(e)	8. CONTRACT OR GRANT NUMBER(#)								
J.D. Jarrell and R.E. Englebretson	N00228-81-C-H361								
9. PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS								
Science Applications, Inc.	PE 63207N PN 7W0513								
2999 Monterey-Salinas Highway	TA CC00 NEPRF WU 6.3-14								
Monterey, CA 93940	12. REPORT DATE								
Naval Air Systems Command	August 1982								
Department of the Navy	13. NUMBER OF PAGES								
Washington, DC 20361	20								
14. MONITORING AGENCY NAME & ADDRESS(II different from Controlling Office)	15. SECURITY CLASS. (of this report)								
Naval Environmental Prediction Research Facility	UNCLASSIFIED								
Monterey, CA 93940	15a. DECLASSIFICATION/DOWNGRADING								
	1								
16. DISTRIBUTION STATEMENT (of this Report)									
Approved for public release; distribution unlimited.									
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)									
IB. SUPPLEMENTARY NOTES									
19. KEY WORDS (Continue on reverse side if necessary and identity by block number,)								
Tropical cyclone									
Typhoon									
1									
20. ASTRACT (Continue on reverse side if necessary and identify by block number)									
Forecast aids are provided for predicting wind									
a tropical cyclone passes within 360 n mi. The fore	cast aids were produced by								
a tropical cyclone passes within 360 n mi. The fore analyzing a data set comprising the ratios of stati	cast aids were produced by on wind values to tropical								
a tropical cyclone passes within 360 n mi. The fore analyzing a data set comprising the ratios of staticyclone center wind values. Ratio values were then	cast aids were produced by on wind values to tropical assigned to the position of								
a tropical cyclone passes within 360 n mi. The fore analyzing a data set comprising the ratios of staticyclone center wind values. Ratio values were then the cyclone center. The 360 n mi radius circle abou	cast aids were produced by on wind values to tropical assigned to the position of the station was divided								
a tropical cyclone passes within 360 n mi. The fore analyzing a data set comprising the ratios of staticyclone center wind values. Ratio values were then	cast aids were produced by on wind values to tropical assigned to the position of the station was divided ean and maximum ratio within								

CONTENTS

1.	Introduction	on	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1
2.	Production	of	Fo	rec	ast	Ai	ds	•	•	•	•	•	•	•	•	•	•	•	•	1
3.	Use of the	For	reca	ast	Ai	ds	•	•	•	•	•	•	•	•	•	•	•	•	•	4
Ref	erence .	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	7
Dis	tribution														_				_	16





1. INTRODUCTION

Forecasting wind conditions at a station during the passage of a tropical cyclone is a critical problem for operational environmentalists. The Air Force has produced forecast aids for predicting mean and maximum peak gusts for several western Pacific Air Force Bases (Pettett, 1980) for periods when a typhoon was within 360 n mi of a base. The need for similar forecast aids for Navy sites was recognized and the Naval Environmental Prediction Research Facility (NEPRF), Monterey, California was requested to produce the aids. Science Applications, Inc., under contract to NEPRF has conducted the research and development involved in producing forecast aid reports for Yokosuka, Japan and Cubi Point, Philippines.

2. PRODUCTION OF FORECAST AIDS

The forecast aids are based on a data period extending from the establishment of a U. S. Navy weather observation program at the station of interest through 1979. This is a 27 year period for Yokosuka (1953-1979) and 25 years for Cubi Point (1955-1979). Best track data for the tropical cyclones were extracted from Joint Typhoon Warning Center (JTWC) records for the periods when a tropical cyclone was within 360 n mi of the station of interest. Aviation hourly observations at three-hour intervals, obtained from the National Climatic Center (NCC), Asheville, NC, were extracted

for the periods identified as having a tropical cyclone within 360 n mi of the station. The best track and weather observations were then merged into a new data base. From this data, ratios of storm center winds to station reported sustained winds were determined and assigned to the storm center position. The 360 n mi radius circle was divided into 71 equal areas (Fig.1).

The ratios identified with each area were summarized and maximum and mean gust ratios and standard deviations were determined. The number of ratios per area (sample size) and cumulative frequency distribution of the ratios were also computed. Computer plots of the gust ratios, sample size and area number values were generated. The gust ratio plots were then subjectively analyzed taking into consideration such factors as sample size for the mean gusts and cumulative distribution frequency for the maximum gusts.

The analyses of the data are presented as isolines which represent the climatological mean or maximum gust to be expected at the station as a percentage of the tropical cyclone center wind. The data base is separated into two classifications of cyclones, i.e., typhoons and lesser tropical cyclones. The classification is based on the

¹Aviation hourly observations are archived at NCC for the local times corresponding to 00,03,06,09,12,15,18,21 GMT only.




Figure 1. A 360 n mi radius circle divided into 71 equal area (5734.5 n mi²) segments which can be centered on the station of interest. The circle is comprised of an inner circle and five surrounding rings. The radial thickness of each ring is approximately 60 n mi, but is not a constant. The segments are numbered from the inner circle and spiral outward.

cyclone center wind speed at the time of the station wind obervation. A set of analyses is provided for each cyclone classification. In addition, a table containing all the data necessary to produce figures 1 through 5 is provided. The data in the table will assist local reanalysis if required.

3. USE OF THE FORECAST AIDS

The forecast aids can be utilized as follows:

center position on the appropriate forecast aid analysis; 2) determine the maximum gust ratio value by interpolating between the contours; and 3) apply this ratio (percentage) to the cyclone center wind value to obtain the maximum or mean gust values to be used as a forecast aid in making the wind forecast. For example, if a tropical cyclone has center winds of 100 kt and a ratio of .65 was determined above, then 65% of the center wind gives forecast gusts to 65 kt for the station.

Sustained one-minute maximum and average wind values can be found by applying a factor of 2/3 to the gust values. This factor is the inverse of the 1.5 to 1 ratio of gusts to sustained winds that was used in the Air Force reports and verified as follows: A study of the wind observations recorded at Cubi Point (1953-1979) and Yokosuka (1955-1979) was made as part of the development of the methodology used in producing these forecast aids. That data set included the

NCC tape archived data, hand augmented with gust data. A uniform ratio of gust to sustained wind speed of 1.5:1 was found over various speed ranges and at both stations. The data set included all station observations (Cubi Point 3449 and Yokosuka 2114) with sustained winds of 10 knots or more when a tropical cyclone was within 360 n mi of the station. This ratio was found to be reasonable for all tropical cyclone intensity classifications and station wind conditions.

Forecasters should recognize that all of the gust information is based on the archived sustained winds (aviation observations at three hour intervals from NCC) multiplied by 1.5. In determining this multiplier, local effects as they relate to various wind directions were only indirectly taken into account. That is, the ratios assigned to each area relate only to storms centered in that area. The storm center location relative to the station location strongly influences the station wind velocity. Therefore, some degree of local effects are inherent in the analyzed ratio patterns.

Table 1 summarizes the data used in producing the forecast aids and other general information. The data in Table 1 is sufficient to reproduce figures 1 through 5 should local reproduction or modifications be desired. The ratio values in Table 1 represent the relationship of station sustained winds to tropical cyclone center winds. To derive

the forecast aids for gust values the 1.5 multiplier must be applied.

Figures 2 through 5 are the forecast aid analyses. The contours are labelled as percentages which were derived from the ratios of station winds to tropical cyclone center winds. Note that the maximum contour values on figures 3 and 5 are less than 100 percent. For example, the mean gust aid for typhoon strength tropical cyclones (Fig. 5) shows only a 70 percent contour around the station. Table 1, segment 1 for tropical cyclones of 64 kt or greater shows 3 cases of typhoon strength centers being located within the area of segment 1. The mean sustained wind to typhoon center wind ratio for the 3 cases is .513 to 1. None of the immediate surrounding areas, segments 2 through 7 (total of 34 cases), have mean ratios as high as area 1. Applying the 1.5 multiplier to the ratios of segments 1 through 7 results in the data that supports the 70 percent contour.

The interpretation of figure 5 is that Yokosuka has not on the average experienced winds at the official observation point of as great an intensity as the official typhoon center winds during typhoon passages. While these findings are based on a reasonable sample size, caution should be used in applying these results when a typhoon center is expected to pass over or very near the station.

Inconsistent gust values will be obtained from the aids when a tropical cyclone center wind change results in a

change of cyclone classification and therefore a change of forecast aid. For example, use of figure 3 for a tropical storm forecast to pass over the station with 60 kt center winds would indicate mean gusts of about 42 kt. A change in center wind to 65 kt and the use of figure 5 indicates about 49 kt mean gusts. An intermediate value is the likely best guidances in such cases.

REFERENCE

Pettett, J.E., 1980: <u>Prediction of Typhoon-Induced Peak</u>
Winds at Four Pacific Stations. lww/TN-80/001.




Figure 2. Maximum Gust Ratios (labelled as percentage) for Yokosuka when a tropical cyclone of less than typhoon strength (<64 kt) is centered within 360 n mi of the station. Locate the typhoon center by latitude and longitude and interpolate the ratio (percentage) value. Multiply the typhoon center wind speed by this percentage to get the wind speed value of the maximum gust expected with the given center position and wind speed. Multiply the maximum gust speed by 0.67 to find the maximum one-minute average sustained wind speed.




Figure 3. Mean Gust Ratios (labelled as percentage) for Yokosuka when a tropical cyclone of less than typhoon strength (<64 kt) is centered within 360 n mi of the station. Locate the typhoon center by latitude and longitude and interpolate the ratio (percentage) value. Multiply the typhoon center wind speed by this percentage to get the wind speed value of the mean gust expected with the given center position and wind speed. Multiply the mean gust speed by 0.67 to find the mean one-minute average sustained wind speed.




Figure 4. Maximum Gust Ratios (labelled as percentage) for Yokosuka when a tropical cyclone of typhoon strength (≥64 kt) is centered within 360 n mi of the station. Locate the typhoon center by latitude and longitude and interpolate the ratio (percentage) value. Multiply the typhoon center wind speed by this percentage to get the wind speed value of the maximum gust expected with the given center position and wind speed. Multiply the maximum gust speed by 0.67 to find the maximum one-minute average sustained wind speed.




Figure 5. Mean Gust Ratios (labelled as percentage) for Yokosuka when a tropical cyclone of typhoon strength (\geq 64 kt) is centered within 360 n mi of the station. Locate the typhoon center by latitude and longitude and interpolate the ratio (percentage) value. Multiply the typhoon center wind speed by this percentage to get the wind speed value of the mean gust expected with the given center position and wind speed. Multiply the mean gust speed by 0.67 to find the mean one-minute average sustained wind speed.

Table 1. A listing of the data used in producing figures 1 through 5, and other general information. Table contents by column are: segment number, latitude and longitude of segment center, maximum ratio, mean ratio, standard deviation of ratios, number of ratios (sample size), and cumulative frequency distribution expressed as the percentage of ratios occurring between 0.0 and the maximum ratio or 1.0 in 0.1 increments.

```
Tropical cylone less than 64 kts
  CENTER POINT
                 MAX MEAN S.DV. N CUM FREQ DIST+N
SEG LAT LONG
  1 35.3 139.7
                .743 .442 .154 10
                                     C 18 28 28 80 96 94 1J8
  RING NUMBER 1
SEG LAT LONG
                 MAX MEAN S.DV.
                                N
                                     CUP FREQ DIST+N
  2 36.5 140.6
                .824 .373 .202
                                13
                                     0 23 54 62 77 85 92 92 104
  3 35.3 141.4
                .714 .427 .152
                                13
                                        8 31 54 69 85 92 100
  4 34.1 140.6
               .630 .437 .104
                                 7
                                     Ũ
                                        C
                                          U 43 71 105
  5 34.1 138.d .547 .350 .191 6 35.3 138.u .690 .492 .096
                                5
                                     20 20 40 60 60 100
                                13
                                      a
                                        0
                                            0 31 62 85 100
  7 36.5 138.8 1.057 .636 .185
                                 7
                                      3
                                         C
                                            Ð
                                               8 29 29 86 86 86 133
  RING NUMPER 2
                                     CUM FREQ DIST+N
                 MAX MEAN S.DV. N
SEG LAT LONG
  8 37.6 146.6
                .896 .471 .243
                                  3
                                      0 0 33 67 67 67 67 120
                .588 .260 .176
                                     21 50 71 71 86 1CJ
  9 36.7 142.1
                                14
                                 9
                .607 .278 .168
                                     11 33 67 78 89 89 100
 10 35.3 142.7
                               15
 11 33.9 142.1
                .767 .415 .198
                                     0 27 27 47 60 87 93 100
                .750 .371 .198
 12 33.0 140.6
                                12
                                     17 25 33 67 75 83 92 100
                .848 .491 .225
                                      0 17 33 33 50 67 83 83 100
 13 33.0 138.3
                                6
                                      8 31 62 92 92 10J
 14 33.9 137.3
                .520 .264 .114
                                13
 15 35.3 136.7
                .933 .478 .198
                                25
                                      3 4 23 40 63 76 88 92 92 103
 16 36.7 137.3 1.000 .537 .278
                                10
                                      0 0 30 50 50 70 74 80 80 100
 17 37.6 138.8
               .698 .591 .116
                                      C
                                        C
                                           0 25 25 50 100
                                 4
  RING NUMBER 3
                 MAX MEAN S.DV.
                                     CUM FREQ DIST+N
SEG LAT LONG
                                 N
                                 2
 18 38.7 146.6
                .444 .397 .048
                                      0 0 0 50 100
                .548 .310 .116
 19 38.0 142.4
                                  8
                                      0 13 63 88 88 105
                .240 .155 .05C
                                     0 80 100
 20 36.8 143.5
                                 5
 21 35.3 144.0
                •679 •319 •169
                                 7
                                      2 29 57 86 86 86 100
                .465 .338 .137
                                 5
                                     20 20 20 63 100
 22 33.8 143.5
                                 7
 23 32.6 142.4
                .630 .446 .140
                                      E 14 14 43 43 100
 24 31.9 140.6
                .647 .421 .165
                                15
                                      7 13 13 40 53 93 100
                .522 .234 .124
                                     13 53 73 87 93 100
 25 31.9 138.8
                                15
                                     18 18 36 73 91 91 91 100
 26 32.6 137.0
                .800 .342 .199
                                11
                                      6 35 76 en 94 94 94 94 94 103
 27 33.8 135.9
                .957 .275 .198
                                17
                .750 .385 .177
                                      6 18 29 47 82 88 94 166
 28 35.3 135.4
                                17
 29 36.4 135.9
               .909 .408 .250
                                 6
                                      J 33 33 50 83 83 83 83 83 1J0
 30 38.9 137.6 1.000 .511 .216
                                        G 13 50 53 88 88 88 88 103
                                8
 31 38.7 138.8 .655 .535 .091
                                6
                                      Q
                                         £
                                            0 17 33 83 100
```

```
RING NUMBER 4
                 MAX MEAN S.DV. N
                                    CUM FREQ DIST+N
SEG LAT LONG
 32 39.7 140.7
                                     0 0 0 2 67 67 67 100
                .800 .556 .173
                                 3
                                     14 14 43 71 100
 33 39.2 142.4
                                 7
               .500 .309 .125
               .225 .142 .065
                                 3
                                     33 67 100
 34 38.2 143.9
 35 36.8 144.9
               .100 .163 .037
                                 2
                                     100
                                  9
                                     33 56 67 67 78 103
 36 35.3 145.2
                .553 .256 .194
                                     17 33 58 75 83 100
 37 33.8 144.9
                .567 .294 .154
                                12
                                      [ 17 17 50 67 163
               .600 .418 .146
                                 6
 38 32.4 143.9
                                      7 33 53 67 73 93 93 100
 39 31.4 142.4
               .727 .336 .189
                                15
                                     17 25 33 67 92 103
 40 30.9 146.7
                .533 .333 .150
                                12
 41 30.9 138.7
               .500 .238 .110
                                13
                                      8 46 69 92 100
 42 31.4 137.0
               .490 .214 .136
                                21
                                     33 48 76 90 130
 43 32.4 135.5
                                     38 56 88 100
                .343 .171 .092
                                16
                                     18 36 73 73 73 100
 44 33.8 134.5
                .603 .274 .184
                                11
               .700 .381 .147
                                13
                                     45 35.3 134.2
               .850 .501 .179
                                5
                                        6 17 50 50 83 83 83 100
 46 36.8 134.5
 47 38.2 135.5
               .560 .327 .181
                                      0 33 67 67 67 100
                                 3
                                5
                                        0 20 60 80 103
 48 39.2 137.6
               .600 .426 .112
                                     G
 49 39.7 138.7
               .571 .371 .130
                                      J 0 50 75 75 103
 RING NUMBER 5
SEG LAT LONG
                 MAX MEAN S.DV. N
                                    CUM FREQ DIST+N
50 46.7 146.7
                                 5
                                         0 20 20 80 103
                .600 .434 .128
                                    G
51 40.3 142.5
               .400 .381 .027
                                 3
                                      ũ
                                         0 0 100
                                 5
                                     20 40 83 80 130
52 39.4 144.1
                .414 .219 .120
                                3
                                    33 67 198
               .229 .147 .663
53 38.3 145.4
                                12
               .286 .161 .572
                                     25 67 133
54 36.8 146.2
 55 35.3 146.4
                                 9
                                    33 78 78 89 89 89 100
               .633 .197 .181
                                      2 33 56 78 89 106
                                 9
 56 33.8 146.2
                .566 .316 .127
                                     33 60 80 100
57 32.3 145.4
               .400 .175 .110
                                15
                                     25 67 92 100
58 31.2 144.1
               .314 .181 .084
                                12
                                     25 75 88 109
59 30.3 142.5
               .375 .178 .096
                                 - 8
                                    17 33 50 50 83 100
                .600 .315 .181
                                 6
60 29.9 146.7
                .880 .267 .194
                                     18 47 71 82 94 94 94 94 100
61 29.9 138.7
                                17
62 30.3 136.9
               .444 .252 .121
                                15
                                     13 44 63 88 100
               .632 .336 .148
                                15
                                     7 27 43 60 93 93 100
63 31.2 135.3
               ·667 ·288 ·157
                                21
                                     14 19 57 86 90 90 100
64 32.3 134.0
65 33.8 133.2
                .500 .257 .121
                                    19 25 69 88 130
                                16
66 35.3 133.0
                .567 .206 .168
                                    33 67 67 89 89 163
                                9
               .579 .357 .146 5
                                     0 20 40 80 80 100
67 36.8 133.2
               .615 .376 .211 5
                                    20 26 40 69 60 80 100
68 38.3 134.0
                                7
               .64J .369 .131
69 39.4 135.3
                                    3 C 43 71 86 86 100
70 40.7 136.9 .565 .427 .121 6 0 0 17 50 67 100 71 40.7 138.7 1.100 .501 .308 8 13 13 13 50 63 63 75 88 88 100
```

```
Tropical cyclones of 64 kt or greater
 CENTER POINT
                MAX MEAN S.DV. N CUM FREQ DISTAN
SEG LAT LONG
  1 35.3 139.7 .714 .513 .209 3
                                  ũ
                                      $ 33 33 33 67 67 100
 RING NUMBER 1
                MAX MEAN S.DV. N CUM FREQ DISTAN
SEG LAT LONG
 2 36.5 140.6 .360 .216 .144
                               2
                                  50 50 50 100
                              5
  3 35.3 141.4
              .486 .342 .125
                                   0 20 40 60 100
                              9
                                  0 11 11 33 44 103
  4 34.1 140.6 .587 .458 .117
 5 34.1 138.8 .514 .313 .132 12
                                  8 17 59 58 92 100
 6 35.3 138.0 .585 .401 .146 4
                                  0 0 50 50 75 100
              .400 .392 .008
                               2
 7 36.5 138.8
                                   ũ
                                      8
                                        0 100
 RING NUMBER 2
                MAX MEAN S.DV. N
                                  CUM FREQ DIST+N
SEG LAT
        LONG
                                  50 50 10C
 8 37.6 146.6 .277 .169 .148
                               2
               .187 .133 .842
                                  50 100
 9 36.7 142.1
                               4
                                  15 77 85 100
               .361 .176 .093
                             13
10 35.3 142.7
                                  0 25 42 83 92 103
11 33.9 142.1 .515 .313 .116 12
12 33.0 140.6 .431 .316 .097 14
                                  7 7 36 79 100
                                  9 36 64 100
13 33.0 138.6 .380 .237 .161
                             11
              .354 .209 .1.8
                                  25 50 75 100
14 33.9 137.3
                              8
               .538 .46i .111
                               *
                                  0 0 3 33 33 100
15 35.3 136.7
16 36.7 137.3 .500 .391 .144
                               3
                                  6 33 33 33 100
                               3
17 37.6 138.8
 RING NUMPER 3
                MAX MEAN S.OV.
SEG LAT LONG
                               N
                                 CUM FRED DIST+N
                                   0 9 133
18 38.7 140.6 .243 .243 .610
                               1
19 38.6 142.4
                               7
                                  43 160
20 36.8 143.5 .138 .192 .027
              .377 .377 .GcJ
21 35.3 144.0
                                  100
                               1
                                   $ 50 88 88 1JG
22 33.8 143.5
                                3
              .426 .338 .273
                               4
                                   C C 75 75 10G
23 32.6 142.4
              .493 .256 .397
                                  0 38 81 94 130
24 31.9 140.6
                              15
                                   3 63 75 105
25 31.9 138.8
              .394 .238 .175
                              8
26 32.6 137.0
                              9 44 67 100
               .278 .126 .099
                                  20 46 60 80 90 100
27 33.8 135.9
              .538 .242 .153
                              13
26 35.3 135.4 .514 .285 .203
                              3
                                  33 33 33 67 67 100
                              2 0 0 0 50 100
29 36.8 135.9 .477 .417 .360
30 38.0 137.0 .471 .390 .082
                              2 0 0 3 50 100
31 36.7 138.8 .319 .268 .051
                              2 0 0 50 100
```

```
RING NUMBER 4
                 MAX MEAN S.CV. N CUM FREQ CIST+N
SEG LAT LONG
                                     3 8 130
 32 39.7 140.7
                .238 .238 .000
                                  2
 33 39.2 142.4
                .092 .377 .015
                                     130
                                  2
 34 38.2 143.9
                .185 .164 .021
                                      E 10C
                .185 .100 .045
 35 36.8 144.9
                                  6
                                     E7 100
 36 35.3 145.2
                .366 .193 .082
                                  8
                                     13 50 88 100
                .304 .295 .C09
                                  2
                                         0 50 100
 37 33.8 144.9
                                     0
                .375 .222 .121
                                 12
                                     33 33 58 100
 38 32.4 143.9
                                 9
                                     22 56 67 100
 39 31.4 142.4
                .347 .201 .104
 40 30.9 140.7
                .325 .196 .385
                                 14
                                     21 64 79 100
 41 30.9 138.7
                .289 .164 .078
                                 9
                                     22 56 100
                                     29 64 86 100
 42 31.4 137.0
                .338 .165 .094
                                 14
                                     46 85 85 92 92 1CC
 43 32.4 135.5
                .508 .148 .127
                                 13
 44 33.8 134.5
                .343 .284 .659
                                  2
                                      0 6 53 108
                                  3
 45 35.3 134.2
 46 36.8 134.5
 47 38.2 135.5
                .325 .254 .555
                                  ?
                                      0 33 67 100
                                      0 100
 48 39.2 137.0
                .186 .186 .003
                                  1
 49 39.7 138.7
                .457 .322 .123
                                  4
                                      0 25 50 50 100
  RING NUMBER 5
                 MAX MEAN S.DV. N CUM FREQ DIST+N
    LAT LONG
SEG
 50 46.7 140.7
                .200 .200 .000
                                     0 109
                                  1
                                  2
                                    50 50 100
51 40.3 142.5
                .267 .163 .104
                .062 .062 .030
                                     106
 52 39.4 144.1
                                  1
                                  2
 53 38.3 145.4
                .378 .365 .013
                                     100
                                     75 100
 54 36.8 146.2
                .138 .086 .031
                                  4
                                     46 100
                .179 .107 .644
                                  5
 55 35.3 146.4
                .275 .210 .047
 56 33.8 146.2
                                  8
                                     0 38 100
 57 32.3 145.4
                .291 .201 .972
                                  7
                                     14 43 103
                                     9 36 91 190
 58 31.2 144.1
                .301 .211 .669
                                 11
 59 30.3 142.5
                .200 .108 .952
                                 13
                                     £2 100
                .338 .150 .095
                                 13
                                     40 70 90 100
 60 29.9 146.7
 61 29.9 138.7
                .317 .146 .£84
                                 19
                                     42 68 95 190
62 30.3 136.9
                .366 .164 .196
                                 23
                                     26 65 91 100
                                     10 70 90 100
63 31.2 135.3
                .385 .176 .CA6
                                10
64 32.3 134.C
                .357 .163 .091
                                 15
                                     25 69 94 103
                .200 .133 .059
                                     29 100
                                 7
65 33.8 133.2
                                      0 50 100
                                  2
66 35.3 133.0
                .232 .239 .522
                                 3
                                      3 33 100
67 36.8 133.2
                .295 .237 .545
68 38.3 134.0
                                  )
69 39.4 135.3
                .244 .244 .0.0
                                  1
                                      0 0 103
                .200 .200 .000
                                      0 150
70 40.3 136.9
                                  1
71 40.7 138.7
```

DISTRIBUTION

COMMANDER
U.S. NAVAL FORCES, JAPAN
FPO SEATTLE 98762

COMMANDER IN CHIEF U.S. PACIFIC FLEET PEARL HARBOR, HI 96860

COMSEVENTHFLT FLEET METEOROLOGIST, N3OW FPO SAN FRANCISCO 96601

COMMANDER
AMPHIBIOUS GROUP 1
ATTN: METEORO. OFFICER
FPO SAN FRANCISCO 96601

COMMANDING OFFICER
USS CONSTELLATION (CV-64)
ATTN: MET. OFFICER, OA DIV.
FPO SAN FRANCISCO 96635

COMMANDING OFFICER
USS CORAL SEA (CV-43)
ATTN: MET. OFFICER, OA DIV.
FPO SAN FRANCISCO 96632

COMMANDING OFFICER
USS ENTERPRISE (CVN-65)
ATTN: MET. OFFICER, OA DIV.
FPO SAN FRANCISCO 96636

COMMANDING OFFICER
USS KITTY HAWK (CV-63)
ATTN: MET. OFFICER, OA DIV.
FPO SAN FRANCISCO 96634

COMMANDING OFFICER
USS MIDWAY (CV-41)
ATTN: MET. OFFICER, OA DIV.
FPO SAN FRANCISCO 96631

COMMANDING OFFICER
USS RANGER (CV-61)
ATTN: MET. OFFICER, OA DIV.
FPO SAN FRANCISCO 96633

CHIEF, ENV. SVCS. DIV. OJCS (J-33) RM. 2877K, THE PENTAGON WASHINGTON, DC 20301

NAVAL DEPUTY TO THE ADMINISTRATOR, NOAA RM. 200, PAGE BLDG. #1 3300 WHITEHAVEN ST. NW WASHINGTON, DC 20235

OFFICER IN CHARGE
NAVOCEANCOMDET
U.S. NAVAL AIR FACILITY
FPO SEATTLE 98767

OFFICER IN CHARGE U.S. NAVOCEANCOMDET APO SAN FRANCISCO 96519 COMMANDING OFFICER
USS BLUE RIDGE (LCC-19)
ATTN: MET. OFFICER
FPO SAN FRANCISCO 96628

COMMANDING OFFICER
USS NEW ORLEANS (LPH-11)
ATTN: MET. OFFICER
FPO SAN FRANCISCO 96627

COMMANDING OFFICER
USS OKINAWA (LPH-3)
ATTN: MET. OFFICER
FPO SAN FRANCISCO 96625

COMMANDING OFFICER
USS TRIPOLI (LPH-10)
ATTN: MET. OFFICER
FPO SAN FRANCISCO 96626

COMMANDING OFFICER
USS TARAWA (LHA-1)
ATTN: MET. OFFICER
FPO SAN FRANCISCO 96622

COMMANDING OFFICER
USS BELLEAU WOOD (LHA-3)
ATTN: MET. OFFICER
FPO SAN FRANCISCO 96623

COMMANDING OFFICER
USS PELELIU (LHA-5)
ATTN: MET. OFFICER
FPO SAN FRANCISCO 96624

COMMANDING OFFICER
USS POINT LOMA (AGDS-2)
ATTN: MET. OFFICER
FPO SAN FRANCISCO 96677

CINCPAC BOX 13 STAFF CINCPAC J37 CAMP SMITH, HI 96861

CHIEF OF NAVAL OPERATIONS (OP-952) U.S. NAVAL OBSERVATORY WASHINGTON, DC 20390

COMMANDING OFFICER (10) U.S. NAVOCEANCOMFAC FPO SEATTLE 98762

COMMANDER
NAVAIRSYSCOM
ATTN: LIBRARY, AIR-00D4
WASHINGTON, DC 20361

COMMANDER
NAVAIRSYSCOM, AIR-33
WASHINGTON, DC 20361

COMMANDER
NAVAIRSYSCOM
MET. SYS. DIV., AIR-553
WASHINGTON, DC 20360

NAVAL POSTGRADUATE SCHOOL METEOROLOGY DEPT., CODE 63 MONTEREY, CA 93940 OFFICER IN CHARGE NAVOCEANCOMDET MONTEREY, CA 93940

COMMANDING OFFICER
NORDA, CODE 101
NSTL STATION
BAY ST. LOUIS, MS 39529

COMNAVOCEANCOM NSTL STATION BAY ST. LOUIS, MS 39529

COMNAVOCEANCOM ATTN: J. OWNBEY, N542 NSTL STATION BAY ST. LOUIS, MS 39529

COMMANDING OFFICER
NAVWESTOCEANCEN
BOX 113
PEARL HARBOR, HI 96860

COMMANDING OFFICER NAVEASTOCEANCEN MCADIE BLDG. (U-117) NAVAL AIR STATION NORFOLK, VA 23511

COMMANDING OFFICER
U.S. NAVOCEANCOMCEN
BOX 12. COMNAVMARIANAS
FPO SAN FRANCISCO 96630

DIRECTOR (12)
DEFENSE TECH. INFORMATION
CENTER, CAMERON STATION
ALEXANDRIA, VA 22314

THE EXECUTIVE DIRECTOR AMERICAN METEORO. SOCIETY 45 BEACON ST. BOSTON, MA 02108

AMERICAN METEORO. SOCIETY METEORO. & GEOASTRO. ABSTRACTS P.O. BOX 1736 WASHINGTON, DC 20013

DIRECTOR, JTWC BOX 17 FPO SAN FRANCISCO 96630

WORLD METEOROLOGICAL
ORGANIZATION, ATS DIV.
ATTN: N. SUZUKI
CH-1211, GENEVA 20
SWITZERLAND

DIRECTOR, ROYAL OBSERVATORY NATHAN ROAD, KOWLOON HONG KONG, B.C.C.

LIBRARY
METEORO. RESEARCH INSTITUT
1-1, NAGAMINE, YATABE-MACHI,
TSUKUBA-GUN
IBARAKI-KEN 305 JAPAN

COMMANDER AWS/DN SCOTT AFB, IL 62225

USAFETAC/TS SCOTT AFB, IL 62225

3350TH TECH. TRNG GROUP TTGU/2/STOP 623 CHANUTE AFB. IL 61868

AFGL/LY HANSCOM AFB, MA 01731

5WW/DN LANGLEY AFB, VA 23665

OFFICER IN CHARGE SERVICE SCHOOL COMMAND DET. CHANUTE/STOP 62 CHANUTE AFB, IL 61868

HQ 1ST WEATHER WING/DN HICKAM AFB, HI 96853

DET 17, 30 WS APO SAN FRANCISCO 96328

CHIEF AEROSPACE SCIENCE BRANCH HQ 1ST WW (MAC) HICKAM AFB, HI 96853

TYPHOON RESEARCH LABORATORY ATTN: LIBRARIAN METEORO. RESEARCH INSTITUT 1-1 NAGAMINE, YATABE-MACHI, TSUKUBA-GUN IBARAKI-KEN, 305, JAPAN

MARITIME METEOROLOGY DIV. JAPAN METEOROLOGICAL AGENCY OTE-MACHI 1-3-4 CHIYODA-KU TOKYO, JAPAN

HYDROGRAPHIC DEPARTMENT MARITIME SAFETY AGENCY 3-1, TSUKIJI 5-CHOME TOKYO, JAPAN

JAPAN METEOROLOGICAL AGENCY 3-4 OTEMACHI 1-CHOME, CHIYODA-KU TOKYO 100, JAPAN

WEATHER CENTRAL SERVICE SQ. JASDF FUCHU, TOKYO, JAPAN

COORDINATOR, ESCAP/WMO
TYPHOON COMMITTEE SECRETARIAT
C/O UNDP
MANILA, PHILIPPINES